



COMPACT FORM FACTOR.
COMPACT PRICE.
BALANCES TO .02 MICRON.

PUSH QUALITY.
PUSH THROUGHPUT
FOR LESS.

Model SB-1000 Dynamic Balancing System

Dual functionality at an economical price.

The **SB-1000** is an easy to use, compact dynamic balancing system that provides full functionality, including both an automatic and a manual balancing mode, at an entry-level price.

This single machine control provides exceptional accuracy, capable of balancing to a tolerance as low as 0.02 microns peak-to-peak displacement over a spindle range of 300 to 30,000 RPM. With its digital design and intuitive icon-driven user interface, the SB-1000 is simple to install on existing equipment and can be easily integrated through the grinding machine CNC/PLC hardware interface.

The SB-1000's Manual Balance mode not only provides the most economical manual balancing solutions, it also provides real-time display of vibration and RPM levels. Operators can set alert and alarm thresholds through the CNC/PLC interface.

Operators can also utilize the Automatic Balance mode with the addition of a balance head and cable for rapid balance cycles controlled through the CNC/PLC interface, eliminating the need for operator interaction.

BENEFITS:

- The functionality of two products in one
- Increases throughput by saving setup time
- Improves part quality by automatically balancing to as low as 0.02 microns
- Change balance mode with the push of a button
- All-digital design increases operating life and reliability
- Compact and easy to install and operate
- Economical price
- Longer life for grinding wheels, dressing wheels and spindle bearings
- Works with all SBS installations and accessories
- Easy CNC/PLC interface; USB 2.0 communication capability for firmware upgrades
- Backed by world-class and worldwide customer service



SPECIFICATIONS

Physical

Display:

OLED Graphical Display

User Interface:

Universal icon-driven (language independent)

Dimensions:

W x H x D: 210 mm x 112 mm x 33 mm

SB-5500 Compatible:

Operates with existing balancers/cables, sensors, CNC/PCL hardware interface

Power Input Requirements

Power Supply:

24 VDC with terminal block connection, and M5 ground stud

Input voltage:

+ 22VDC to + 26VDC at 3,5A max.

Surge protected

Negative protected (reverse protected from a non-grounded supply)

Fused

Communications Interfaces:

USB 2.0 (firmware upgrades only), CNC/PLC hardware interface (opto-isolated outputs)

Performance

RPM Reporting:

300 to 30,000 RPM

Wide Vibration Range:

50 μ g to 1,25 g

Vibration Display Resolution:

Four digit display with up to 2 decimal points in microns, with display resolution to 0.01 μ m

Vibration Display Repeatability:

6,000 RPM $\pm 1\%$ @ 5,0 μ m

300–30,000 RPM $\pm 2\%$ @ 50:1 signal to noise

Vibration Display Accuracy:

6,000 RPM $\pm 2\%$ @ 5,0 μ m

300–30,000 RPM $\pm 4\%$ @ 50:1 signal to noise

Auto-Balance Resolution:

0.02 microns displacement at 6,000 RPM

Vibration Filter:

Custom digital filter has bandwidth +/- 3 % of measurement RPM

Safety and Environmental

- CE certified
- RoHS compliant

Environmental and Installation Conditions:

- Pollution degree 2
- Intended for indoor use only
- Installation category I
- IP54, NEMA 12
- Environmental temperature range: 5 °C to +55 °C
- Humidity: 0 to 85 % relative humidity (non-condensing) throughout temperature range

For more information on SBS products, see accretechsbs.com to find your local SBS distributor or Representative, or call ACCRETECH.



ACCRETECH (Europe) GmbH
Landsberger Straße 396
81241 Munich, Germany
info@accretech.eu
Phone: +49 89 546788-0